

# D-TRACKER X


**BLUE**

**GREEN**

Please note the image shown above is for illustration purposes only.

<b>Specifications</b>			
<b>ENGINE</b>		<b>FRAME</b>	
Type	Liquid-cooled, 4-stroke, Single cylinder, DOHC, 4 valves	Type	Tubular, Semi-double cradle
Displacement	249 cm <sup>3</sup>	Caster (rake)	25.5°
Bore and Stroke	72.0 mm x 61.2 mm	Tyre:	
Compression Ratio	11.0:1	a) Front	110/70-17 M/C 54S Tube type
Performance:		b) Rear	130/70-17 M/C 62S Tube type
a) Maximum power	18.0 kW @ 9,000 rpm	<b>SUSPENSION</b>	
b) Maximum torque	21.0 N.m @ 7,000 rpm	Front: Type	Telescopic fork
Fuel System	Digital Fuel injection KEIHIN single barrel Ø34	Rear: Type	Swingarm (Uni-trak)
Ignition	CDI	<b>BRAKES</b>	
Starting	Electric	Front: Type	Single disc brake
Lubrication	Forced lubrication (wet sump)	Rear: Type	Single disc brake
<b>DRIVE TRAIN</b>		<b>DIMENSIONS</b>	
Transmission	6-speed, Constant mesh, Return shift	Overall length	2,130 mm
Gear ratios:		Overall width	795 mm
1st	3.000 (30/10)	Overall height	1,125 mm
2nd	2.000 (30/15)	Wheelbase	1,420 mm
3rd	1.500 (27/18)	Ground clearance	225 mm
4th	1.190 (25/21)	Seat height	860 mm
5th	1.050 (21/20)	Curb mass	138 kg
6th	0.952 (20/21)	Fuel capacity	7.7 liters
Final reduction ratio	2.786 (39/14)		
Clutch	Wet multi-disc		

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.