

ER-6f



Green



Black

Please note the above image(s) shown above is for illustration purposes only.

SPECIFICATIONS

ENGINE		FRAME	
Type	Liquid-cooled, 4-stroke, Parallel Twin, DOHC, 8 valves	Type	Diamond, high-tensile steel
Displacement	649 cm ³	Caster (rake)	25°
Bore and Stroke	83 mm x 60 mm	Tyre:	
Compression ratio	10.8:1	a) Front	120/70-ZR17M/C (58W) Tubeless
Performance:		b) Rear	160/60-ZR17M/C (69W) Tubeless
a) Maximum power	53.0 kW (72.1 PS) @ 8,500 rpm	SUSPENSION	
b) Maximum torque	66.0 N·m (6.7 kgf·m) @ 7,000 rpm	Front: Type	41mm telescopic fork
Fuel system	Fuel injection: ø38 mm x 2 (KEIHIN)	Rear: Type	Offset laydown single-shock with adjustable preload
Starting	Electric	BRAKES	
Ignition	Battery and coil (transistorized)	Front: Type	Dual semi-floating 300mm petal discs, Dual piston caliper
Lubrication	Forced lubrication (semi-dry sump)	Rear: Type	Single 220 mm petal disc, Single piston caliper
DRIVE TRAIN		DIMENSIONS	
Transmission	6-speed, Return	Overall length	2110 mm
Gear ratios:		Overall width	760 mm
1st	2.438 (39/16)	Overall height	1200 mm
2nd	1.714 (36/21)	Wheelbase	1410 mm
3rd	1.333 (32/24)	Ground clearance	145 mm
4th	1.111 (30/27)	Seat height	790 mm
5th	0.966 (28/29)	Curb mass	204 kg
6th	0.852 (23/27)	Fuel capacity	15.5 litres
Final reduction ratio	3.067 (46/15)		
Clutch	Wet multi disc, Manual		

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.