

## J300 ABS


**BLACK**

**WHITE**

Please note the image shown above is for illustration purposes only.

### Specifications

ENGINE		FRAME	
Type	Liquid-cooled, 4-stroke Single	Type	Tube diamond, Steel
Displacement	299 cm <sup>3</sup>	Caster (rake)	28°
Bore and Stroke	67.0 mm x 45.1 mm	Tyre:	
Compression Ratio	10.8:1	a) Front	120/80-14M/C 58S
Performance:		b) Rear	150/70-13M/C 64S
a) Maximum power	20.3 kW {28PS} / 7,750 rpm	SUSPENSION	
b) Maximum torque	28.7 N.m {2.9kgf.m} /6,250 rpm	Front: Type	ø37 mm telescopic fork
Fuel System	Fuel injection: ø34 mm x 1	Rear: Type	Twin shocks with 5-way adjustable preload
Ignition	ECU Control (Full Transistor)	BRAKES	
Starting	Electric	Front: Type	Single ø260 mm petal discs
Lubrication	Forced lubrication, wet sump	Caliper	Dual-piston
DRIVE TRAIN		Rear: Type	Single ø240 mm petal disc
Transmission	CVT with centrifugal clutch	Caliper	Dual-piston
Final Drive	Belt	DIMENSIONS	
Primary reduction ratio	2.220 ~ 0.790	Overall length	2,235 mm
Final reduction ratio	7.222 (43/16 x 43/16)	Overall width	775 mm
		Overall height	1,260 mm
		Wheelbase	1,555 mm
		Ground clearance	145 mm
		Seat height	775 mm
		Curb mass	191 kg
		Fuel capacity	13 litres

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.