KSR PRO







GREEN

Please note the image shown above is for illustration purposes only.

Specifications			
ENGINE		FRAME	
Туре	Liquid-cooled, 4-stroke, Single cylinder, SOHC, 2 valves	Type Caster (rake)	Tube Back Bone 26°
Displacement	111 cm³	Tyre:	
Bore and Stroke	53.0 mm x 50.6 mm	a) Front	100/90-12 49J Tubeless
Compression Ratio	9.5:1	b) Rear	100/90-12 49J Tubeless
Performance:			
a) Maximum power	6.4kW {8.7PS} @ 8,500 rpm	SUSPENSION	
b) Maximum torque	8.4 N.m {0.86kgf.m} @ 6,000 rpm	Front: Type	Ø30mm Telescopic fork
Fuel System	Carburetor: KEIHIN PB18	Rear: Type	Swingarm single shock
Ignition	Digital DC-CDI		
Starting	Electric	BRAKES	
Lubrication	Forced lubrication (wet sump)	Front: Type	Single 200mm disc
		Rear: Type	Single 184mm disc
DRIVE TRAIN			
Transmission	4-speed,Return	DIMENSIONS	
Gear ratios:		Overall length	1,725 mm
1st	3.000 (36/12)	Overall width	740 mm
2nd	1.938 (31/16)	Overall height	1,020 mm
3rd	1.350 (27/20)	Wheelbase	1,170 mm
4th	1.087 (25/23)	Ground clearance	225 mm
Final reduction ratio	2.214 (31/14)	Seat height	750 mm
Clutch	Wet multi-disc, Manual	Curb mass	94 kg
		Fuel capacity	7.3 liters

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.