

# Ninja 250


**GREEN**

**WINTER EDITION**

Please note the image shown above is for illustration purposes only.

## Specifications

ENGINE		FRAME	
Type	Liquid-cooled, 4-stroke, DOHC, 8 Valves	Type	Tube diamond, steel
Displacement	249cm <sup>3</sup>	Caster (rake)	26°
Bore and Stroke	62.0mm x 41.2mm	Tyre:	
Compression Ratio	11.3:1	a) Front	110/70-17M/C 54S
Performance:		b) Rear	140/70-17M/C 66S
a) Maximum power	23.5 kW {32PS} / 11,000 min <sup>-1</sup>	SUSPENSION	
b) Maximum torque	21.0 N.m {2.1kgf.m} / 10,000 min <sup>-1</sup>	Front: Type	ø37mm Telescopic fork
Fuel System	Fuel injection KEIHIN ø28 x 2	Rear: Type	Bottom-Link Uni-Trak with gas charged shock and 5-Way adjustable preload
Ignition	Digital	BRAKES	
Starting	Electric	Front: Type	Single ø290mm petal disc
Lubrication	Forced lubrication (wet sump)	Rear: Type	Single ø220mm petal disc
DRIVE TRAIN		DIMENSIONS	
Transmission	6-speed, Return	Overall length	2,010mm
Gear ratios:	Chain	Overall width	715mm
1st	2.600 (39/15)	Overall height	1,110mm
2nd	1.789 (34/19)	Wheelbase	1,400mm
3rd	1.409 (31/22)	Ground clearance	140mm
4th	1.160 (29/25)	Seat height	785mm
5th	1.000 (27/27)	Curb mass	172kg
6th	0.893 (25/28)	Fuel capacity	17 litres
Final reduction ratio	3.286 (46/14)		
Clutch	Wet multi-disc, manual		

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.