

NINJA 250 SL



GREEN

Please note the image shown above is for illustration purposes only.

Specifications			
ENGINE		FRAME	
Type	Liquid-cooled, 4-stroke Single	Type	Tube diamond
Displacement	249cm ³	Caster (rake)	24.0°
Bore and Stroke	72.0 x 61.2mm	Tyre:	
Compression Ratio	11.3:1	a) Front	100/80-17M/C 52S
Performance:		b) Rear	130/70-17M/C 62S
a) Maximum power	20.6 kW {28 PS} / 9,700 rpm	Wheel travel: front	110mm
b) Maximum torque	22.6 N.m {2.3 kgf.m} / 8,200 rpm	rear	116mm
Fuel System	Fuel injection: ø38mm x 1	Steering angle (left/right)	36° / 36°
Ignition	Digital	SUSPENSION	
Starting	Electric	Front: Type	Ø37mm telescopic fork
Lubrication	Forced lubrication, wet sump	Rear: Type	Uni-Trak with adjustable spring preload
DRIVE TRAIN		BRAKES	
Transmission	6-speed, Return	Front: Type	Single Ø290mm disc
Final Drive:	Chain	Caliper	Dual piston
Gear ratios:		Rear: Type	Single Ø220mm disc
1st	3.000 (33/11)	Caliper	Dual piston
2nd	1.933 (29/15)	DIMENSIONS	
3rd	1.444 (26/18)	Overall length	1,935mm
4th	1.217 (28/23)	Overall width	685mm
5th	1.045 (23/22)	Overall height	1,075mm
6th	0.923 (24/26)	Wheelbase	1,330mm
Final reduction ratio	3.000 (42/14)	Ground clearance	165mm
Clutch	Wet multi-disc, manual	Seat height	780mm
		Curb mass	151kg
		Fuel capacity	11 litres

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.