

Z125 PRO


LIME GREEN

ORANGE

Please note the image shown above is for illustration purposes only.

Specifications			
ENGINE		FRAME	
Type	Air-cooled, 4-stroke Single	Type	Backbone, high-tensile steel
Displacement	125 cm ³	Caster (rake)	26.0°
Bore and Stroke	56.0 x 50.6 mm	Tyre:	
Compression Ratio	9.8:1	a) Front	100/90-12 49J
Valve System	SOHC, 2 Valves	b) Rear	120/70-12 51L
a) Maximum power	7.2 kW {9.8 PS} / 8,000 min ⁻¹	Wheel travel: front	100 mm
b) Maximum torque	9.6 N.m {0.98 kgf.m} / 6,000 min ⁻¹	rear	104 mm
Fuel System	Fuel injection: ø24 mm x 1	Steering angle (left/right)	42° / 42°
Ignition	Digital	SUSPENSION	
Starting	Electric	Front: Type	ø30 mm inverted fork
Lubrication	Forced lubrication, wet sump	Rear: Type	Offset laydown single-shock with adjustable preload
DRIVE TRAIN		BRAKES	
Transmission	4-speed, return	Front: Type	Single ø200 mm petal disc
Final Drive:	Chain	Caliper	Single-piston
Primary Reduction Ratio	3.409 (75/22)	Rear: Type	Single ø184 mm petal disc
Gear ratios:		Caliper	Single-piston
1st	3.000 (36/12)	DIMENSIONS	
2nd	1.938 (31/16)	Overall length	1,700 mm
3rd	1.350 (27/20)	Overall width	750 mm
4th	1.087 (25/23)	Overall height	1,005 mm
Final reduction ratio	2.143 (30/14)	Wheelbase	1,175 mm
Clutch	Wet multi-disc, manual	Ground clearance	155 mm
		Seat height	780 mm
		Curb mass	101 kg
		Fuel capacity	7.4 litres

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.