

Z900 ABS



GREY



BLUE (SPECIAL EDITION)

Please note the image shown above is for illustration purposes only.

Specifications	
ENGINE	
Type	Liquid-cooled, 4-stroke In-Line Four, DOHC, 16 Valves
Displacement	948 cm ³
Bore and Stroke	73.4 x 56.0 mm
Compression Ratio	11.8:1
Performance:	
a) Maximum power	92.2 kW {125 PS} / 9,500 min ⁻¹
b) Maximum torque	98.6 N.m {10.1 kgf.m} / 7,700 min ⁻¹
Fuel System	Fuel injection ø36 mm X 4 with sub-throttles
Ignition	Digital
Starting	Electric
Lubrication	Forced lubrication, wet sump
DRIVETRAIN	
Transmission	6-speed, Return
Finaldrive	Chain
Gear ratios:	
1st	2.692 (35/13)
2nd	2.059 (35/17)
3rd	1.650 (33/20)
4th	1.409 (31/22)
5th	1.222 (33/27)
6th	1.034 (30/29)
Final reduction ratio	2.933 (44/15)
Clutch	Wet multi-disc, Manual
FRAME	
Type	Trellis, high-tensile steel
Caster (rake)	24.5°
Tyre:	
a) Front	120/70ZR17M/C (58W)
b) Rear	180/55ZR17M/C (73W)
SUSPENSION	
Front: Type	ø41 mm inverted fork with rebound damping and spring preload adjustability
Rear: Type	Horizontal Back-link with rebound damping and spring preload adjustability
BRAKES	
Front: Type	Dual semi-floating ø300 mm petal discs
Caliper	Dual opposed 4-piston
Rear: Type	Single ø250 mm petal disc
Caliper	Single-piston
DIMENSIONS	
Overall length	2,115 mm
Overall width	825 mm
Overall height	1,065 mm; 1,140 mm (Special Edition)
Wheelbase	1,450 mm
Ground clearance	130 mm
Seat height	795 mm
Curb mass	210 kg; 213kg (Special Edition)
Fuel capacity	17 litres

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.